



Tunnelling Asia' 2022

International Conference on
Underground Space : The Need of the Day



ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN

AITES

ITA
INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION

INFLUENCE OF CONSTRUCTION METHODS IN DESIGN APPROACH

by

Dr. Rakesh Kumar (PhD IIT Delhi)

UV GLOBAL CONSULT

uvglobaldesign@gmail.com



Tunnelling Asia' 2022

International Conference on Underground Space : The Need of the Day



ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN


AITES

ITA
INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION

INTRODUCTION

•Methods of Tunneling

- Conventional Drill and Blast
- Cut and Cover
- New Austrian Tunneling Method (NATM)/SEM
- Tunnel Boring Machine (TBM)





Tunnelling Asia' 2022

International Conference on Underground Space : The Need of the Day



ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN

AITES

ITA
INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION

Conventional Tunnelling

- Tunnel is excavated using drill and blast method
- Depending upon tunnel diameter, heading and benching is decided
- Tunnel is supported using shotcrete, rock bolts/anchors, steel ribs, lattice girders
- Tunnel lining Plain or reinforced is installed
- Drainage arrangement, curtain and consolidation grouting, water proofing



June 27th – 28th 2022, Mumbai, India



Tunnelling Asia' 2022

International Conference on Underground Space : The Need of the Day




ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN

AITES

ITA
INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION

Cut & Cover Tunnel

- Tunnel is excavated using sheetpiles, diaphragm walls, soldier piles, secant piles
- Lateral support by struts, walers, anchors
- Then structure/tunnel is constructed
- Then the tunnel is backfilled



June 27th – 28th 2022, Mumbai, India



Tunnelling Asia' 2022

International Conference on Underground Space : The Need of the Day



ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN


AITES

ITA
INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION

NATM Method

Basic principles of NATM

- (i) Mobilization of rock mass strength,
- (ii) Shotcrete protection to preserve the load-carrying capacity of the ring of rock mass,
- (iii) Monitoring the deformation of the excavated rock mass,
- (iv) Providing flexible but active supports and
- (v) Closing of invert to form a load-bearing support ring to control deformation of the rock mass.





Tunnelling Asia' 2022

International Conference on Underground Space : The Need of the Day

















ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN

ITA

INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION

AITES

TUNNEL BEHAVIOUR TYPES			
St	Stable ground: Stable tunnel section with local gravity failures. Rock mass is compact with limited and isolated discontinuities		
Br	Brittle failure: Brittle failure or rock bursting at great depths		
Wg	Wedge failure: Wedge sliding or gravity driven failures. Insignificant strains. The rock mass is blocky to very blocky, blocks can fall or slide. The stability is controlled by the geometrical and mechanical characteristics of the discontinuities. The ratio of rock mass strength to the in situ stress (α_{cm}/p_c) is high ($>0.6-0.7$) and there are very small strains ($\epsilon < 1\%$)		
Ch	Chimney type failure: Rock mass is highly fractured, maintaining most of the time its structure (or at least that of the surrounded rock mass). Rock mass does not have good interlocking (open structure) and in combination with low confinement (lateral stress) can tend to block falls which develop to larger overbreaks of chimney type. The overbreaks may be stopped and "bridged" by better quality rock masses, depending on the in situ conditions. This type may be applied also in cases of brecciated and disintegrated rock mass in ground with high confinement (high lateral stress)		
Rv	Ravelling ground: The rock mass is brecciated and disintegrated or foliated with practically zero cohesion and depending on the intact rock interlocking (Rv1 case: without infilling) and possible secondary hosted geomaterial, (Rv2 case: with infilling, e.g. clay), rock mass can generate immediate rock mass ravelling in face and tunnel perimeter. The difference with Ch type lies in the block size, which is very small here, the self-supporting, which is very limited here and the failure extension, where it is unrestricted due to the lack of better rock mass quality in the surrounding zone		
Fl	Flowing ground: The rock mass is disintegrated with practically zero cohesion and intense groundwater presence along the discontinuities. Rock fragments flow with water inside the tunnel		
Sh	Shear failure: Minor to medium strains, with the development of shear failures close to the perimeter around the tunnel. Rock mass is characterized by low strength intact rocks ($\sigma_{ci} < 15\text{MPa}$) while the rock mass structure reduces the overall the rock mass strength. Strains develop either at a small to medium tunnel cover (around 50-70m) in case of poor sheared rock masses, or in larger cover in case of better quality rock masses. The ratio of rock mass strength to the in situ stress (α_{cm}/p_c) is low ($0.3 < \alpha_{cm}/p_c < 0.45$) and strains are measured or expected to be medium (1-2.5 %)		







	measured or expected to be medium (1-2.5 %)		
Sq	Squeezing ground: Large strains, due to overstepping with the development of shear failures in an extended zone around the tunnel. Rock mass consists of low strength intact rocks while the rock mass structure reduces the overall rock mass strength. The ratio of rock mass strength to the in situ stress (α_{cm}/p_c) is very low ($\alpha_{cm}/p_c < 0.3$) and strains are measured or expected to be $>2.5\%$, and they can be also take place at the face		
Sw	Swelling ground: Rock mass contains a significant amount of swelling minerals (montmorillonite, smectite, anhydrite) which swell and deform in the presence of groundwater. Swelling often occurs in the tunnel floor when the support ring is not fully closed		
San	Anisotropic strains: The rock mass is stratified or schistose or consists of specific weak zones and develops increased strain characteristics along a direction defined by the schistosity.		

Fig. 11 Schematic diagram of tunnel behavior after Marinos [31]



Tunnelling Asia' 2022

International Conference on Underground Space : The Need of the Day




ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN

AITES

ITA
INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION

TBM Tunnels

- Tunnel is excavated by TBM, earth balancing, slurry, shield type
- Rock/soil support in form of rock bolts, shotcrete and segmental lining
- Consolidation, curtain grouting, water proofing



June 27th – 28th 2022, Mumbai, India



Tunnelling Asia' 2022

International Conference on
Underground Space : The Need of the Day



ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN

AITES

ITA

INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION

Various Analysis

- i. Numerical techniques like FEM, FDM, DEC can be used for analysis of cavities with any possible geometrical shape, properties and support system
- ii. Rock mass/soil is modeled using a mesh of Finite elements of appropriate size and spacing
- iii. Joints can also be modeled using interface elements
- iv. Mohr-Coulomb/Hoek-Brown or any other failure criterion can be used based on strata properties
- v. Groundwater and pore pressures can be simulated along with seismic loads (if required)
- vi. Stage wise softening , tunnel excavation & support installation can be simulated
- vii. 3D modeling can include realistic effect of confinement loss in face-ahead of tunnel cavity

June 27th – 28th 2022, Mumbai, India



Tunnelling Asia' 2022

International Conference on Underground Space : The Need of the Day Input Parameters for Analysis



ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN
AITES

ITA
INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION

- ▶ Strength Parameters (c, phi, tensile strength, Dilatancy)
- ▶ Deformations parameters (E, v)
- ▶ Joint Parameters (c, phi, normal and shear stiffness)
- ▶ Permeability
- ▶ Density
- ▶ In-situ stresses

June 27th – 28th 2022, Mumbai, India



Tunnelling Asia' 2022

International Conference on
Underground Space : The Need of the Day





ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN

ITA

INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION

AITES

Basic Concept





Tunnelling Asia' 2022

International Conference on Underground Space : The Need of the Day



ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN

ITA

INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION

AITES

Loads and Ground Reaction Curves





Fig. 1. – Terzaghi's ground arch concept. Reproduced from "Rock defects and loads on tunnel supports" published in 1946.

the radial convergence δ both increase as the support pressure decreases as illustrated in Fig. 2. Eventually, about two tunnel diameters behind the face, the support pressure p_i provided by the face has decreased to zero and the radial convergence δ reaches its final value.





Tunnelling Asia' 2022

International Conference on Underground Space : The Need of the Day



ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN

AITES

ITA
INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION

Table 1: Rockmass Parameters for Class V/ Shear Zone

Description		Unit	Very Poor Rockmass/ Shear Zone
Intact Rock Properties	UCS	MPa	50
	GSI		15
	mi		9
	Ei	MPa	30000
	ν		0.25
Rock Mass Parameters	c (peak)	MPa	0.34
	Φ (peak)	deg	30.66
	c (residual)	MPa	0.22
	Φ (residual)	deg	22.01
	Tensile Strength	MPa	0.009
	Deformation Modulus	MPa	1093.47
Rock Mass Parameters Damage Zone (1 m for class V/ Shear zone)	c	MPa	0.141
	Φ	deg	14.863
	Tensile Strength	MPa	0.002
	Deformation Modulus	MPa	700.555

June 27th – 28th 2022, Mumbai, India



Tunnelling Asia' 2022

International Conference on Underground Space : The Need of the Day



ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN

AITES

ITA
INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION

Unsupported

Floor wedge [2] FS: stable Weight: 0.464 MN	Upper Right wedge [6] FS: 2.359 Weight: 0.116 MN	Upper Left wedge [7] FS: 0.662 Weight: 0.335 MN	Near End wedge [9] FS: 4.645 Weight: 0.155 MN
Far End wedge [10] FS: 40.758 Weight: 0.172 MN			

Supported

Floor wedge [2] FS: stable Weight: 0.464 MN	Upper Right wedge [6] FS: 10.014 Weight: 0.116 MN	Upper Left wedge [7] FS: 5.531 Weight: 0.335 MN	Near End wedge [9] FS: 4.645 Weight: 0.155 MN
Far End wedge [10] FS: 40.758 Weight: 0.172 MN			

June 27th – 28th 2022, Mumbai, India



Tunnelling Asia' 2022

International Conference on Underground Space : The Need of the Day



ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN


AITES

ITA
INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION

Hydro-geological conditions affect tunnel stability

- Additional water pressures are exerted
- Extreme conditions negatively affect durability of supports and strength of rock mass
- Drainage has to be provided to allow water to release. Drainage pumps have to be used in case of heavy flow
- Confined aquifers encountered during construction are dangerous & may cause flooding

Geo-composite application





Tunnelling Asia' 2022

International Conference on Underground Space : The Need of the Day



ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN
ITA
INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION




Figure 1: Stereographic Projection of Joints and Tunnel Alignment with Tunnel Direction of N225.30°




Figure 2: Alignment, Position and Factor of Safety of Wedges without Support System for Tunnel direction of N225.30°




Figure 11: Discretization Boundary for Rock Classes I-IV




Figure 12: Discretization Boundary for Rock Class V




Figure 13: Major Principal Stress Contours for Rock Class I



Tunnelling Asia' 2022

International Conference on Underground Space : The Need of the Day




ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN

ITA
INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION

AITES

i. Bartons' "Q" system method





Tunnelling Asia' 2022

(ii). Support system based on RMR

International Conference on Underground Space : The Need of the Day



ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN

AITES

ITA
INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION

The RMR support table (for tunnels with 10m span)

Ground class	Excavation (drill and blast)	Rock support		
		Rock bolts (20 mm diam., fully bonded)	Shotcrete	Steel sets
1. Very good rock RMR: 81-100	Full face: 3m advance	Generally no support required except for occasional spot bolting		
2. Good rock RMR: 61-80	Full face: 1.0 - 1.5m advance; Complete support 20 m from face	Locally bolts in crown, 3m long, spaced 2.5m with occasional wire mesh	50mm in crown where required	None
3. Fair rock RMR: 41-60	Top heading and bench: 1.5 - 3m advance in top heading; Commence support after each blast; Commence support 10 m from face	Systematic bolts 4m long, spaced 1.5 - 2m in crown and walls with wire mesh in crown	50 - 100mm in crown, and 30mm in sides	None
4. Poor rock RMR: 21-40	Top heading and bench: 1.0 - 1.5m advance in top heading; Install support concurrently with excavation - 10 m from face	Systematic bolts 4 - 5m long, spaced 1 - 1.5m in crown and walls with wire mesh	100 - 150mm in crown and 100mm in sides	Light ribs spaced 1.5m where required
5. Very poor rock RMR < 21	Multiple drifts: 0.5 - 1.5m advance in top heading; Install support concurrently with excavation; shotcrete as soon as possible after blasting	Systematic bolts 5 - 6m long, spaced 1 - 1.5m in crown and walls with wire mesh. Bolt invert	150 - 200mm in crown, 150mm in sides, and 50mm on face	Medium to heavy ribs spaced 0.75m with steel lagging and forepoling if required. Close invert

June 27th – 28th 2022, Mumbai, India



Tunnelling Asia' 2022

International Conference on Underground Space : The Need of t



ASSOCIATION
INTERNATIONALE DES TUNNELIERS
ET DE L'ESPACE SOUTERRAIN


AITES

ITA

INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION



MX (local)
kNm/m

<= -196
-178
-159
-141
-122
-103
-84.9
-66.2
-47.6
-29
-10.4
8.17
26.8
45.4
64
82.6
>= 101



Modeling in Staad pro
& final lining drawing

LINING CAPACITY PLOT



June 27th – 28th 2022, Mumbai, India



Tunnelling Asia' 2022

International Conference on Underground Space : The Need of the Day



ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN
ITA
INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION

Numerical Models for Hard Ground and Soft Ground




Figure 11: Discretization Boundary for Rock Classes I-IV




Figure 12: Discretization Boundary for Rock Class V





Figure 13: Major Principal Stress Contours for Rock Class I






Tunnelling Asia' 2022

International Conference on Underground Space : The Need of the Day



ASSOCIATION
INTERNATIONALE DES TUNNELIERS
ET DE L'ESPACE SOUTERRAIN
ITA
INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION

Numerical
Models for
Hard Ground
and Soft
Ground





Tunnelling Asia' 2022

International Conference on Underground Space : The Need of the Day





ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN

ITA
INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION

AITES

Typical Support System for Soft Ground





Tunnelling Asia' 2022

International Conference on Underground Space : The Need of the Day




ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN

AITES

ITA
INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION

Segmental Concrete lining



- Normally segmental precast concrete segments used in soils, boulders & weak rock masses. The TBM is capable of placing them in position all around a circular tunnel with the help of a segment erector.
- Increased speed of construction
- Tapered rings for curve alignment & simultaneous grouting with tunneling
- Water tightness - extremely important and double gasket system and hydrophobic sealing is used
- Provides structural capacity to resist ground, water pressure and reaction frame to push TBM ahead (if TBM used)

June 27th – 28th 2022, Mumbai, India



Tunnelling Asia' 2022

International Conference on Underground Space : The Need of the Day



ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN

AITES

ITA
INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION



Load cases to be considered:

1. Ground & Groundwater loads
2. Loads produced by maximum Desirable deflection
3. TBM Propulsion jacking loads
4. Grouting loads (Annulus & secondary grouting)
5. Seismic loads
6. Handling & Stacking loads

ULS : Check for failure by Max. Bending Moment or min. thrust couple (for all loads)

SLS: Check against cracking by Max. Bending moment & Thrust couple (for Load 1,2&4)

Ground & Groundwater analysis: Elastic analysis (Curtis/Muir wood);
Or FEM analysis (Flac, Plaxis etc.)





Tunnelling Asia' 2022



International Conference on Underground Space : The Need of the Day




ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN

ITA
INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION

AITES



Reinforcement Design





Tunnelling Asia' 2022

International Conference on

The Need of the Day



ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN

AITES


ITA
INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION



Load cases to consider are:	Reinforcement Bars		
	Circumferential	Longitudinal	Radial
Ground and groundwater loads	SC	-	Nominal
Loads induced by maximum deflection	SC	-	Nominal
TBM propulsion jacking loads	-	SC	S/T
Grouting loads	SC	-	Nominal
Effects of poor ring build	SC	SC	S/T
Seismic loads	SC	SC	S/T
Handling and stacking loads	B	-	-

SC - Design as Short Column
B - Design as Beam
S/T - Design for Shear and Tension loads

Reinforcement Design – Circumferential bars:



- ◆ Results from continuum analyses for ground/water loading
- Results from Plaxis analysis
- Results from analysis of grouting loads
- ▲ Results from results of birds-mouthing analysis
- Results from distortion analysis
- ▲ Results from jacking forces analysis (refer to Calc: 03-4&/CG/C/S509)

June 27th – 28th 2022, Mumbai, India



Tunnelling Asia' 2022

International Conference on Underground Space : The Need of the Day



ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN
AITES

ITA
INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION

Instrumentation and Monitoring in SEM/NATM

Essential component of NATM is Instrumentation and Monitoring

1. During & prior to tunnel excavation

- Standpipe piezometers, extensometers are installed along tunnel alignment to account for sudden change in GW level and subsidence

2. During Excavation and Installation of Primary Support System

To check deformations, convergences and stresses in primary support system

- Optical Targets/ Bi reflex targets/Displacement targets
- Extensometers MPBX/Tape Extensometers, Measuring anchors
- Pressure cells, Stress meters, Load cells, inclinometers
- Piezometers

After final lining

- For long term stability monitoring of tunnel and structures on ground.

During construction, monitoring is done very frequently (fortnightly, weekly, daily). After construction monitoring frequency is reduced.

June 27th – 28th 2022, Mumbai, India



Tunnelling Asia' 2022

International Conference on Underground Space : The Need of the Day



ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN

ITA
INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION

Tunnel Convergence




Fig. 12: Tunneling problems associated with different levels of strain.



Tunnelling Asia' 2022

Geotechnical Monitoring Section

International Conference on Underground Space : The Need of the Day



ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN


ITA

INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION

AITES

- Displacement targets
- MA....Measuring anchor
- E.....Extensometer
- SM....Strainmeter
- PC....Pressure cells

1. Alert Limit: 50-60% of predicted deformation
2. Attention Limit: 70-80% of predicted deformation
3. Alarm Limit: 95 to 100% of predicted deformation



June 27th – 28th 2022, Mumbai, India




Tunnelling Asia' 2022

International Conference on Underground Space : The Need of the Day



ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN
ITA
INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION





Tunnelling Asia' 2022

International Conference on Underground Space





Bi-Reflex Target



MPBX anchor & rods



Load cell & its arrangement With rock bolt





Tunnelling Asia' 2022

International Conference on Underground Space : The Need of the Day



ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN
ITA
INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION

Some Examples





Tunnelling Asia' 2022

International Conference on Underground Space : The Need of the Day



ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN
ITA
INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION

Some Examples





Tunnelling Asia' 2022

International Conference on Underground Space : The Need of the Day



ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN

ITA
INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION

Some Examples





Tunnelling Asia' 2022

International Conference on Underground Space : The Need of the Day



ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN

AITES

ITA
INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION

References:

- [1] E. Hoek, "Support for very weak rock associated with faults and shear zones, International Symposium on Rock Support and Reinforcement Practice in Mining, Kalgoorlie, Australia," 14-19 March 1999, pp. 20.
- [2] E. Hoek, and P. Marinos, "Predicting tunnel squeezing problems in weak heterogeneous rock masses," Tunnels and Tunnelling International, in press 2000.
- [3] E. Hoek, "Big tunnels in bad rock," ASCE Journal of Geotechnical and Geo environmental Engineering, Sept 2001, Vol. 127, No. 9, pp. 726-740.



Tunnelling Asia' 2022

International Conference on
Underground Space : The Need of the Day



ASSOCIATION
INTERNATIONALE DES TUNNELS
ET DE L'ESPACE SOUTERRAIN
AITES

ITA
INTERNATIONAL TUNNELLING
AND UNDERGROUND SPACE
ASSOCIATION

Thanks for Kind Attention

uvglobaldesign@gmail.com